


标记 Mark	次数 No.	更改文件号 File change No.	更改内容 Content changed	签名 Signature	日期 Date

Dimension: (Unit: mm)



Common Rating


Step angle	1.8°
Position accuracy	1.8±0.09°
Dielectric strength	500VAC 1min
Insulation resistance	100MΩ(500VDC)
Insulation class	B
Temp rise(Max)	80K
Radial play	Max.0.02mm(Load 450g)
Axial play	Max.0.08mm(Load 900g)

Specification:

Current/phase	2.5 A
Voltage	2.5 V
DC Resistance/phase ±10%	1.0 Ω
Inductance/phase ±20%	2.4 mH
Holding torque	0.8 N·cm
Inertia	0.11 kg·cm ²
Weight	0.45 kg
Reduction ratio	1:20

黑色热缩管
φ6x35mm

Motor Connctions:



技术要求:
1、未注形位公差按GB/T 1184-K;
2、未注尺寸公差按GB/T 1804-m。
(除非另外指定)

设计 Designed	杨陶	2021-10-09	标准化 Standardized		材料(Material):	名称(Title)	开环步进电机
制图 Drawn	杨陶	2021-10-09				型号(Model)	42CM08-RD20 MS20
校对 Proofread			审核 Checked	王洪松	2021-10-09	重量(Weight)/g:	图号(DWG No.)
工艺 Processed			批准 Approved	袁建建	2021-10-09	阶段标记(Stage Mark)	料号(Part No.)
表单编号 Form No.	LS-MT-01-07B		版本/版次 Edition/Serial NO.	A/01	共1页第1页	比例(Scale)	1:1



雷赛智能
Leadshine